
3000 Series

Compact Utility Tractors








There are tractors. And there are the kind John Deere makes—legendary machines with contemporary designs, well-forged parts, and highly sophisticated features. Ever since John Deere himself invented the self-scouring plow in 1837, we have always focused on bringing a better product to our customers. No piece of equipment quite defines

John Deere like the tractor. Starting with the introduction of the Waterloo Boy back in 1918, John Deere set the benchmark for the modern-day tractor for the remainder of the 20th century. Starting with two-cylinder designs that would be a trademark of the brand, John Deere continuously improved and evolved its tractor line. And by the end of the 1960s,







1944 Tractor with starter

4- & 6-cylinder tractors introduced



John Deere would secure its place as the largest farm tractor company in the world. We also realized that tractors were more than just for farming. That's why, in the early 1990s, we dedicated an entire factory in Augusta, Georgia, for the sole purpose of producing compact utility tractors. Our first tractors rolled off the assembly line in 1993, giving

folks with multiple acres the ability to do a variety of mid- to large-sized jobs. With over 200 available implements, our 3000 Series Tractors can help you get more done than you could ever imagine. Read on to find the tractor that's right for you.



The performance you demand, the comfort you deserve.

It's a difference you can tell from the moment you sit down—this is not tractor as usual. With the John Deere 3000 TWENTY Series, you can see that the attention to detail is something special. Start with AutoHST™. This auto-like transmission option for the 3520 and 3720 makes operating these tractors as easy as driving to the grocery store. All you have to do is press a single foot pedal to go forward and shift to reverse using a hand lever. And, with the eHydro™ transmission, performance is never an issue with the Performance Tracking System. It accurately monitors the tractor's functions and systems, giving you instant feedback for quick diagnosis. Throw in additional features like the LoadMatch™ electronic power management system, the Quik-Park[™] loaders, and standard 4WD and you have three tractors that are without peers.









STANDARD FEATURES AND OPTIONS

Transmission

AutoHST™

- Familiar car-like control layout
- Engine speed controlled with single pedal
- Automotive Cruise, SpeedMatch™ and MotionMatch™ customize speed to any application
- Shift lever on the console for forward, neutral and reverse
- Available on the 3520 and 3720 open station tractors

eHydro™

Effortless two-pedal automatic transmission. With easy shifting from forward to reverse at the touch of a pedal, it's ideal for everything from loading to mowing. Automotive Cruise, SpeedMatch™ and MotionMatch™ customize speed to any application. Plus, there's a LoadMatch™ power management system.

PowrReverser™

Convenient dash-mounted lever makes this manual transmission easy to shift from forward to reverse without clutching—a noticeable benefit when loading.

Other options

- Electro-hydraulic 3rd SCV
- Electric diverter/2 add'l rear hydraulic couplers
- 4th/5th independent SCVs (open station only)
- Power beyond hydraulics
- A-frame front hitch
- Air ride seat
- Automotive-style cruise control (eHydro and AutoHST)

- Canopy
- Hydraulic mower lift
- Mid PTO
- Sunshade umbrella
- Top-and-tilt kit for 3-point hitch
- Vertical exhaust
- AutoConnect[™] mid-mower deck
- ComfortGard[™] Cab
- iMatch Quick-Hitch
- iMatch AutoHltch

DIMENSIONS



WHEELBASE: 68 in. (1727 mm)

LENGTH: 120.2 in. (3053 mm)




MIN. WIDTH: 40.6 in. (1030 mm)

WIDTH: 68.4 in. (1737 mm)

Room with a view.

It could be a long, hot, dusty day. Or it could be cold, wet, or freezing. Either way, you don't care, since you're sitting in the ultimate comfort of a John Deere TWENTY Series cab. Six adjustable vents are strategically placed to keep you at the optimum temperature, winter, spring, summer, or fall. And this "room" is so tightly sealed, even most dust particles or allergens can't make their way inside. So come in, shut the door, and get ready to work in absolute perfect conditions.



1 Visibility:

Unique raised header bar, four-post design and high seat placement enable 360-degree views for safer maneuvering.

2 Climate control:

Roof-mounted system offers 15,000 BTUs of cooling and 30,000 BTUs of heating for year-round comfort.

3 Allergen protection:

ComfortGard[™] cab keeps out dust and clippings—as well as microscopic allergens.

4 Right-hand control center:

Levers and controls are within easy reach for more efficient operating.

Automotive features:

Just like a car, the John Deere 3000 TWENTY Series Tractors provide optional features to keep you comfortable.

- · Cup holder
- Arm rest

5

- 2-speed windshield wiper
- Sun visor
- Stereo with iPod[™] dock
- Automotive cruise control (set, resume, accelerate, decelerate)
- · Automotive-style hand parking brake



STANDARD FEATURES AND OPTIONS

Standard cab features

- Air conditioning and heat
- Forward work lights
- Front windshield wiper
- Deluxe cloth seat
- Integrated radio antenna
- Sun visor
- Right-hand control center
- Exclusive raised header bar
- Available R1, R3, R3 fine turf, R4 tires
- Cab speaker kit

Other options

- Deluxe air-ride seat
- Dual external rearview mirrors
- AM/FM radio w/ CD and iPod™ dock
- Beacon light
- Back up alarm
- Front fender kit
- Rear fender extension kit
- Rear work light kit
- Electro-hydraulic 3rd SCV
- Electric divert/2 add'l rear hydraulic couplers

True commercial-grade backhoes mount and dismount easily. Bucket rotation of 180 degrees is perfect for trenching without leaving behind spillage. Now available on cab and open station models.




Deluxe air-ride seat

provides superior cushioning for a consistently smooth, comfortable ride over the roughest terrain. Highly recommended for commercial users.



Not just a good view, a vista.

With a combination of high seat placement, curved sides and few obstructions, you have a commanding 360° view to the front, either side, and to the rear.



Get it on. And get on with it.

Time. You only have so much of it, especially on the weekend. So when you want to work with an implement, you don't want to spend precious time wrestling with it. So that's why we considerably shortened the time between starting up your tractor and getting work done with the iMatch AutoHitch, Quik-Park loaders, and AutoConnect decks.



iMATCH™ AUTOHITCH™



IMATCH™ AUTOHITCH™

Stay in your seat. This exclusive, patent-pending coupling system allows you to effortlessly attach rear-mounted, PTO-driven implements without getting out of the seat. Use your imagination. Mowing, rotary cutting, blading and grading, tilling or aerating—you won't find a simpler way to get more done.

- To quickly change implements with the iMatch Quick-Hitch, you simply back in, hydraulically lift the unit and secure the latches.
- Once you're connected and the unit is in place, there's an even easier way to automatically hook up PTO-driven attachments. The iMatch AutoHitch is the answer. To hook up the drive shaft to the secure unit, just rotate the handle, turn and pull AutoHitch lever.
- Prive off.

Quality that won't surprise you—but the price will.

Our 3E Series Tractors were built with the notion that, if you excel in the areas that matter the most, you'll exceed expectations as well. That's why the 3032E and 3038E have extremely efficient diesel engines that feature impressive torque reserves that allow you to take on punishing loads. You'll also be surprised to find a hydrostatic transmission with Twin Touch[™] pedals instead of a gear version. Power steering also comes standard, which makes maneuvering a breeze. Standard differential lock and 4WD give you the traction you need over rugged terrain. And a fixed ROPS is certified and easily fits under a seven-foot garage door.







DIMENSIONS

Shown with optional iMatch Quick-Hitch



MIN. WIDTH: 23.9 in. (608 mm

WIDTH: 56.5 in. (1434 mm)



WHEELBASE: 60 in. (1525 mm)

LENGTH: 111 in. (2820 mm)

00D HEIGHT: 51.8 in. (1315 n

We're pushing the limits of what a standard tractor can do.

Take your notion of what a standard tractor is supposed to be and replace it with what it could be—the John Deere 3005. This nononsense workhorse exceeds expectations at every turn, with a price that demands a double-take. A cast-iron transmission supplies the strength and durability you need when using a loader or backhoe attachment. Effortless power steering and standard 4WD make for tight turns. And logic and ergonomics go hand-in-hand with the at-your-fingertips controls. No longer does owning a standard tractor mean having to settle for less. Not with the 3005.







3005 | 3032E | 3038E | 3320 | 3520 | 3720

IM	PL	ΕN	ЛEI	NTS
IIVI		171	415	

	3003	303ZE	3030L	3320	3320	3720
BACKHOES	•			•	•	•
BOX BLADES	•	•	•	•	•	•
BROADCAST SPREADERS	•	•	•	•	•	•
CORE AERATORS	•	•	•	•	•	•
DISK HARROWS	•	•	•	•	•	•
FLAIL MOWERS					•	•
FRONT BLADES	•	•	•	•	•	•
GROOMING MOWERS	•	•	•	•	•	•
GROOMING MOWERS, REAR DISCHARGE		•	•			
IMATCH AUTO HITCHES	•	•	•	•	•	•
LANDSCAPE RAKES	•	•	•	•	•	•
LOADERS	•	•	•	•	•	•
MANURE SPREADERS	•	•	•	•	•	•
AUTO CONNECT MID-MOUNT MOWERS				•	•	•
OVERSEEDERS	•	•	•	•	•	•
PENDULAR SPREADERS				•	•	•
POSTHOLE DIGGERS BY ROTOMEC	•	•	•	•	•	•
PULVERIZERS	•	•	•	•	•	•
REAR BLADES	•	•	•	•	•	•
ROTARY BROOMS				•	•	•
ROTARY CUTTERS	•	•	•	•	•	•
ROTARY TILLERS	•	•	•	•	•	•
SICKLEBAR MOWERS				•	•	•
SNOW BLOWERS	•	•	•	•	•	•
WHEEL RAKES	•	•	•	•	•	•
WOOD CHIPPERS	•	•	•	•	•	•
PLOWS	•	•	•	•	•	•



No one builds or backs tractors better than John Deere.

It's the fine print, but a big story: Every John Deere Compact Tractor comes with a 3-year/2000-hour limited warranty. See your dealer for details.*



Specifications

	3005	3032E	3038E
ENGINE			
Туре	Yanmar 3TNV82A	Yanmar 3TNV88	Yanmar 3TNV84T
PTO HP	23.5 (17.5 kW)	25 (18.6 kW)	30 (22.4 kW)
Rated speed, RPM	2,700	2,500	2,500
Engine displacement	81.2 cu. in. (1.3 L)	100 cu. in. (1.64 L)	91.5 cu. in. (1.496 L)
Battery	500 Cold Cranking Amps	500 Cold Cranking Amps	500 Cold Cranking Amps
Alternator	20 Amps	40 Amps	40 Amps
HYDRAULICS			
Steering	4.2 gpm (15.9 L/min)	4.0 gpm (15.1 L/min)	4.0 gpm (15.1 L/min)
Implement	5.4 gpm (20.5 L/min)	5.3 gpm (20 L/min)	5.3 gpm (20 L/min)
Total capacity	9.6 gpm (36.4 L/min)	9.3 gpm (35.5 L/min)	9.3 gpm (35.5 L/min)
Lift capacity (24 in. behind center link)	815 lb. (370 kg)	1,356 lb. (615 kg)	1,356 lb. (615 kg)
TRANSMISSION			
Standard	Collar Shift 8F/2R	Hydrostatic - 2 Range	Hydrostatic - 2 Range
Final drive	Spur gear	Spur gear	Spur gear
Brakes	Dry	Wet disk	Wet disk
Steering	Power	Power	Power
4WD	Optional	Standard	Standard
РТО			
PTO type	Continuous live	Independent	Independent
PTO options	Mid & Rear	Rear	Rear
REAR HITCH			
Туре	Category 1	Category 1	Category 1
Control type	Position	Position	Position
WEIGHT			
With all fluids	2WD 1,930 lb. (875 kg)		
	4WD 2,105 lb. (955 kg)	2,175 lb. (987 kg)	2,175 lb. (987 kg)
LOADER May Unicht Lift Conneity at Divet	7/0 lb //)	1 106 lb (520 la)	1 106 lb /F20 las
Max Height Lift Capacity at Pivot	740 lb. (kg)	1,186 lb. (539 kg)	1,186 lb. (539 kg)

^{*} See the LIMITED WARRANTY FOR JOHN DEERE COMMERCIAL AND CONSUMER EQUIPMENT for details.

	3320	3520	3720
ENGINE			
Гуре	Yanmar 3TNV88	Yanmar 3TNV84T	Yanmar 3TNV84HT
 HP *	2.8 (24.1 kW)	37.1 (27.3 kW)	43.2 (31.8 kW)
PTO HP - Gear Transmission	25.5 (19.0 kW)	30.5 (22.7 kW)	N/A
PTO HP - Hydrostatic Transmission	25 (18.6 kW)	30.0 (22.4 kW)	35 (26.1 kW)
Rated Speed, RPM	2,600	2,600	2,600
Engine displacement	100.0 cu. in. (1.64 L)	91.5 cu. in. (1.5 L)	91.5 cu. in. (1.5 L)
Battery power	500 Cold Cranking Amps	500 Cold Cranking Amps	500 Cold Cranking Amps
Alternator	40 Amps	40 Amps	40 Amps
	· P		· · · · · · ·
HYDRAULICS			
Steering	5.3 gpm (20.0 L/min)	5.3 gpm (20.0 L/min)	5.3 gpm (20.0 L/min)
mplement	8.6 gpm (32.5 L/min)	8.6 gpm (32.5 L/min)	8.6 gpm (32.5 L/min)
Total capacity	13.9 gpm (52.5 L/min)	13.9 gpm (52.5 L/min)	13.9 gpm (52.5 L/min)
Lift capacity (24 in. behind center link)	2,200 lb. (999 kg)	2,200 lb. (999 kg)	2,200 lb. (999 kg)
, ,	, ,	J .	, J,
FRANSMISSION			
Standard	PowrReverser"; 12F/12R	PowrReverser [™] ; 12F/12R	N/A
Optional	eHydro* - 3 Range	AutoHydro ^{*†} or eHydro [*] - 3 Range	AutoHydro or eHydro - 3 Range
Final drive	Spur gear	Spur gear	Spur gear
Brakes	Wet disk	Wet disk	Wet disk
Steering	Power	Power	Power
•			
4WD	Standard	Standard	Standard
РТО			
PTO type	Independent	Independent	Independent
PTO options	Rear standard, mid optional	Rear standard, mid optional	Rear standard, mid optional
REAR HITCH			
Гуре	Category 1	Category 1	Category 1
Control type	Position	Position	Position
WEIGHT (With all fluids)	2,900 lb. (1316 kg)	2,900 lb. (1316 kg)	2,900 lb. (1316 kg)
LOADER (W/300CX) Max Height Lift Capacity at Pivot	1,598 lb. (725 kg)	1,598 lb. (725 kg)	1,598 lb. (725 kg)
ROPS	Folding	Folding	Folding
COMFORTGARD" CAB	Optional	Optional	Optional
CRUISE CONTROL	Standard	Standard	Standard
LOADMATCH"	Standard	Standard	Standard
LOADMATCH" AUTO CRUISE / MOTION MATCH	Standard Optional	Standard Optional	Standard Optional



Total support is standard equipment.

No one can duplicate the support and knowledge of your local John Deere dealer. From the moment you enter a John Deere dealership, you can be sure you're getting the very best in customer assistance. Plus, John Deere dealers are in touch with your local community and understand what it takes to maintain your land. Factory-trained service and parts professionals keep your equipment working as hard as you do. Whether in the John Deere dealership or in the field, you can get your equipment serviced and move on to the next task.

Optional John Deere Maintenance Plan Plus

Peace of mind can be financed for just a few dollars a month with the purchase of your tractor. The John Deere Maintenance Plan Plus includes two at home annual maintenance services with genuine John Deere parts. And an additional year of extended service protection, the same type of coverage as your original warranty.

Exceptional Parts Support

Behind every John Deere is a parts support network to get you the high-quality part you need fast. If your dealer does not have a part in stock, in most cases you can order it by 5 p.m., and have it the next day. Or, order parts online at www.JDParts.JohnDeere.com.

Flexible Available Financing

John Deere Credit has convenient and flexible financing options designed for you. See your dealer for details.



This literature has been compiled for worldwide circulation. While general information, pictures and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specification, design and price of the products described in this literature without notice. John Deere's green and yellow color scheme, the leaping deer symbol, and JOHN DEERE are trademarks of Deere & Company.